Media Information



Opel Insignia: Technical Data Overview

Insignia						
Gasoline engines		1.6 ECOTEC	1.8 ECOTEC	1.6 TURBO ECOTEC	2.0 TURBO ECOTEC	2.8 V6 TURBO ECOTEC
Emission classification		Euro 5	Euro 5	Euro 5	Euro 5	Euro 5
Fuel		Premium	Premium	Premium	Premium	Premium
Number of cylinders/Valves per cylinder		4/4	4/4	4/4	4/4	6/4
Displacement	in cm³	1,598	1,796	1,598	1,998	2,792
Bore	in mm	79.0	80.5	79.0	86.0	89.0
Stroke	in mm	81.5	88.2	81.5	86.0	74.8
Max. output	in kW (hp)	85 (115)	103 (140)	132 (180)	162 (220)	191 (260)
	at rpm	6,000	6,300	5,500	5,300	5,500
Max. torque	in Nm	155	175	230	350	350 (400*)
	at rpm	4,000	3,800	2,200 - 5,400	2,000 - 4,000	1,900 - 4,500
Compression ratio		10.8 : 1	10.5 : 1	8.8 : 1	9.3 : 1	9.5 : 1
Transmission						
6-speed manual		standard	standard	standard	standard	standard
6-speed automatic		-	-	-	option	option
Drive						
FWD		standard	standard	standard	standard	-
AWD		-	-	-	option	standard

^{*} with overboost; ** with mechanical park brake; *** with electrical park brake



Insignia					
Diesel engines		2.0 CDTI ECOTEC	2.0 CDTI ECOTEC	2.0 CDTI ECOTEC	2.0 CDTI BiTurbo ECOTEC
Emission classification		Euro 5	Euro 5	Euro 5	Euro 5
Diesel Particle Filter		standard	standard	standard	standard
Number of cylinders/Valves per cylinder		4/4	4/4	4/4	4/4
Displacement	in cm³	1,956	1,956	1,956	1,956
Bore	in mm	83.0	83.0	83.0	83.0
Stroke	In mm	90.4	90.4	90.4	90.4
Max. output	in kW (hp)	81 (110)	96 (130)	118 (160)	140 (190)
	at rpm	4,000	4,000	4,000	4,000
Max. torque	in Nm	260 (320*)	300 (320*)	350 (380*)	400
	at rpm	1,750 – 2,500	1,750 – 2,500	1,750 – 2,500	1,750 – 2,500
Compression ratio		16.5 : 1	16.5 : 1	16.5 : 1	16.5 : 1
Transmission					
6-speed manual		standard	standard	standard	standard
6-speed automatic		-	option	option	option
Drive					
FWD		standard	standard	standard	as of MY 10
AWD		-	-	-	standard

^{*} with overboost



Insignia Vehicle dimensions in mm	4-door	5-door	Sports Tourer
Length	4,830	4,830	4,908
Width	1,856	1,856	1.856
Width with exterior mirrors	2,084	2,084	2,084
Height (at curb weight)	1,498	1,498	1,520
Wheelbase	2,737	2,737	2,737
Track, front	1,585	1,585	1,585
Track, rear	1,587	1,587	1,587
Turning circle in m	1,007	1,507	1,007
Wall to wall	11.4	11.4	11.4
Curb to curb	10.9	10.9	10.9
Boot dimensions in mm (according to ECIE)	10.0	1010	16.6
Length on floor to rear seat back	1,003	1,003	1,086
Length on floor with rear seat back folded forward	1,895	1,895	1,908
Width between wheel housings	1,027	1,027	1,030
Max. opening width	1,017	950	1,064
Opening height	330	594	684
Boot capacity in liters (according to ECIE)			
Boot to boot cover	500	520	540
With rear seat back folded forward to beneath roof	-	1,465	1,510
Weight and axle loads in kg (according to 70/156/EU)			
Curb weight incl. driver	1,503	1,503	1,660
Permissible gross vehicle weight	2,020	2,035	2,215
Payload	517	532	555
Permissible axle load, front	1,005	1,005	1,045
Permissible axle load, rear	1,050	1,070	1,180
Permissible roof load	100	100	100
Fuel tank capacity (in liters)	70	70	70